

SAFETY DATA SHEET

CLEAR PROTECTIVE LACQUER

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME CLEAR PROTECTIVE LACQUER
 PRODUCT NO. ECPL05L
 SUPPLIER ELECTROLUBE. A division of HK
 WENTWORTH LTD
 KINGSBURY PARK, MIDLAND ROAD
 SWADLINCOTE
 DERBYSHIRE, DE11 0AN
 UNITED KINGDOM
 +44(0)1283 222 111
 +44(0)1283 550 177

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PROPAN-2-OL	200-661-7	67-63-0	60-100%	F;R11 Xi;R36 R67
XYLENE	215-535-7	1330-20-7	10-30%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

3 HAZARDS IDENTIFICATION

Highly flammable. Irritating to eyes. Harmful by inhalation and in contact with skin.

CLASSIFICATION Xn;R20/21. Xi;R36. F;R11.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly.

Provide rest, warmth and fresh air. Get medical attention immediately!

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids.

Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Cool containers exposed to flames with water until well after the fire is out.

SPECIFIC HAZARDS

Irritating gases/vapours/fumes of Carbon dioxide (CO₂). Carbon monoxide (CO).

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Collect with non-combustible absorbent material.

Flush with water. Dike for large spills.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

CLEAR PROTECTIVE LACQUER

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

All handling to take place in well-ventilated area. Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves made of: Butyl rubber. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear Liquid	VAPOUR PRESSURE	4.4 kPa @ 30 °C
COLOUR	Amber	FLASH POINT (°C)	12 CC (Closed cup).
ODOUR	Solvent. Benzene.	FLAMMABILITY LIMIT - LOWER(%)	2.3
SOLUBILITY	Immiscible with water		
RELATIVE DENSITY	0.860 - 0.870 @ 20 °C		
VISCOSITY	25 mPas @ 20 °C		
AUTO IGNITION TEMPERATURE (°C)	>425		
FLAMMABILITY LIMIT - UPPER(%)	44		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with oxidisers or reducing agents. Avoid heat, flames and other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

INGESTION

Narcotic effect. Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause chemical burns in mouth and throat.

SKIN CONTACT

Irritating to skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritating to eyes.

CLEAR PROTECTIVE LACQUER**12 ECOLOGICAL INFORMATION**

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT OR PAINT RELATED MATERIAL		
UN NO. ROAD	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	3YE
CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1263
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	II	EMS	F-E, S-E
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1263	ICAO CLASS	3
AIR PACK GR.	II		

15 REGULATORY INFORMATION

LABELLING



Harmful



Highly Flammable

CONTAINS

XYLENE

RISK PHRASES

R11	Highly flammable.
R36	Irritating to eyes.
R20/21	Harmful by inhalation and in contact with skin.

SAFETY PHRASES

S16	Keep away from sources of ignition - No smoking.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.
S36/37	Wear suitable protective clothing and gloves.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980. Rivers (Prevention of Pollution) Act 1961.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC. System of specific information relating to Dangerous Preparations. 2001/58/EEC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

CLEAR PROTECTIVE LACQUER

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION

CN No 32089010

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE

SEPTEMBER 2005

REV. NO./REPL. SDS GENERATED 4

SDS NO.

10340

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R38	Irritating to skin.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.