



## SAFETY DATA SHEET SCC3 ELASTOMER GEL

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**PRODUCT NAME** SCC3 ELASTOMER GEL

**PRODUCT NO.** EDCE01/05L

**SUPPLIER** ELECTROLUBE. A division of  
HK WENTWORTH LTD  
KINGSBURY PARK, MIDLAND  
ROAD  
SWADLINCOTE  
DERBYSHIRE, DE11 0AN  
UNITED KINGDOM  
+44(0)1283 222 111  
+44(0)1283 550 177  
info@hkw.co.uk

**EMERGENCY TELEPHONE** +44(0)1283 222 111 between 8.30 am - 5.00pm Mon - Fri

### 2 HAZARDS IDENTIFICATION

Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

**CLASSIFICATION** Xn;R20/21. Xi;R38. R10.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
XYLENE	215-535-7	1330-20-7	30-60%	R10 Xn;R20/21 Xi;R38
SILICONE MODIFIED ALKYD			30-60%	-
BENZENE, C10-13-ALKYL DERIVATIVES	267-051-0	67774-74-7	<0.5%	N;R50.

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

### 4 FIRST-AID MEASURES

#### NOTES TO THE PHYSICIAN

Treat symptomatically

#### INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

#### INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Get medical attention immediately!

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists. Use tepid water for rinsing

### 5 FIRE-FIGHTING MEASURES

### SCC3 ELASTOMER GEL

#### EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

#### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

#### STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
		50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

#### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

#### PROTECTIVE EQUIPMENT



#### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

#### RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

#### HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

#### EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

#### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet.

Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin.

When using do not eat, drink or smoke.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid	RELATIVE DENSITY	0.965 @ 20 °c
COLOUR	Amber		
ODOUR	Aromatic.		
SOLUBILITY	Immiscible with water		
BOILING POINT (°C)	137 - 143		

### SCC3 ELASTOMER GEL

FLASH POINT (°C) 27 CC (Closed cup).

#### 10 STABILITY AND REACTIVITY

##### STABILITY

Stable under normal temperature conditions.

##### CONDITIONS TO AVOID

Avoid heat. Avoid contact with oxidisers or reducing agents.

##### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

#### 11 TOXICOLOGICAL INFORMATION

##### GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

##### INHALATION

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

##### INGESTION

Harmful if swallowed. Swallowing concentrated chemical may cause severe internal injury. May cause liver and/or renal damage.

##### SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

##### EYE CONTACT

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

Name	XYLENE
Toxic Dose 1 - LD 50	4300 mg/kg (oral rat)

#### 12 ECOLOGICAL INFORMATION

##### ECOTOXICITY

Not regarded as dangerous for the environment.

Name	XYLENE
LC 50, 96 Hrs, FISH mg/l	2.6-8.4
EC 50, 48 Hrs, DAPHNIA, mg/l	1.0-4.7

#### 13 DISPOSAL CONSIDERATIONS

##### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

#### 14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	3YE
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PAGE NO.	3

**SCC3 ELASTOMER GEL**

<b>IMDG PACK GR.</b>	III	<b>EMS</b>	F-E, S-E
<b>MFAG</b>	See Guide	<b>MARINE POLLUTANT</b>	No.
<b>UN NO. AIR</b>	1263	<b>AIR CLASS</b>	3
<b>AIR PACK GR.</b>	III		

**15 REGULATORY INFORMATION****SYMBOLS**

Harmful

**CONTAINS**

XYLENE

**RISK PHRASES**

R10	Flammable.
R38	Irritating to skin.
R20/21	Harmful by inhalation and in contact with skin.

**SAFETY PHRASES**

S24	Avoid contact with skin.
S51	Use only in well-ventilated areas.
S36/37	Wear suitable protective clothing and gloves.

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

The Control of Substances Hazardous to Health Regulations 1988.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980. Rivers (Prevention of Pollution) Act 1961.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION****REVISION COMMENTS**

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

**ISSUED BY**

Helen O'Reilly

**REVISION DATE**

NOVEMBER 2008

**REV. NO./REPL. SDS  
GENERATED**

4

**SDS NO.**

11412

### SCC3 ELASTOMER GEL

#### RISK PHRASES IN FULL

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.
R50	Very toxic to aquatic organisms.

#### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.