

SAFETY DATA SHEET

HIGH PERFORMANCE ACRYLIC CONFORMAL COATING

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME HIGH PERFORMANCE ACRYLIC CONFORMAL COATING
 PRODUCT NO. EHPA200H
 SUPPLIER ELECTROLUBE. A division of HK
 WENTWORTH LTD
 KINGSBURY PARK, MIDLAND ROAD
 SWADLINCOTE
 DERBYSHIRE, DE11 0AN
 UNITED KINGDOM
 +44(0)1283 222 111
 +44(0)1283 550 177

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+;R12
BUTANONE	201-159-0	78-93-3	10-30%	F;R11 Xi;R36 R66 R67
TOLUENE	203-625-9	108-88-3	30-60%	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

3 HAZARDS IDENTIFICATION

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Vapours may cause drowsiness and dizziness. Extremely flammable. Irritating to eyes and skin.

CLASSIFICATION Xn;R48/20. Rep 3;R63. Xi;R36/38. F+;R12. R67.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.

INGESTION

Not relevant.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Ventilate well.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Provide good ventilation.

HIGH PERFORMANCE ACRYLIC CONFORMAL COATING

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)

PROTECTIVE EQUIPMENT



EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

When using do not eat, drink or smoke. **DO NOT SMOKE IN WORK AREA!****9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol Liquid		
COLOUR	White		
ODOUR	Characteristic		
VOLATILITY DESCRIPTION	Volatile.		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	@ 20 °c	VAPOUR PRESSURE	0.87 kPa @ 25 °c
FLASH POINT (°C)	<0 CC (Closed cup).	AUTO IGNITION TEMPERATURE	410/550
		(°C)	
FLAMMABILITY LIMIT - LOWER(%)	1.8	FLAMMABILITY LIMIT - UPPER(%)	10

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

MATERIALS TO AVOID

Powdered metal. Alkali metals. Alkali earth metals.

11 TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation. May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SKIN CONTACT

Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

EYE CONTACT

Irritating to eyes.

ROUTE OF ENTRY

Inhalation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No data on possible environmental effects have been found. Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

HIGH PERFORMANCE ACRYLIC CONFORMAL COATING

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2.1	ADR CLASS	Class 2.1: Flammable gases.
ADR PACK GROUP	Not Applicable	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PACK GR.	Not Applicable
EMS	F-E; S-U	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
ICAO CLASS	2.1	AIR PACK GR.	Not Applicable

15 REGULATORY INFORMATION

LABELLING



Harmful



Extremely Flammable

CONTAINS

TOLUENE

RISK PHRASES

R12	Extremely flammable.
R36/38	Irritating to eyes and skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63	Possible risk of harm to the unborn child.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S24/25	Avoid contact with skin and eyes.
S36/37	Wear suitable protective clothing and gloves.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution Act 1974.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EEC. Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

CN No 38140090

