

# STATIC DISSIPATIVE WASTE BASKET AND BIN LINERS

Product Code: E5075WB/E5076BL

## PRODUCT DESCRIPTION

This waste paper bin is a high density polyethylene container which does not contain carbon, dyes or additives. It will not tribogenerate, and will dissipate static electricity. For use with this waste basket are Anti-static bin liner.

## PRODUCT USE

The **Static Dissipative Waste Basket** is ideal for cleanrooms, manufacturing, inspection, quality control and research industries.

## FEATURES

- \* The container measures 108- 10<sup>12</sup> ohms for surface resistance
- \* High impact resistance
- \* Will not outgas
- \* Convenient for office or laboratory
- \* Permanently dissipative
- \* Safe to use in solvent areas
- \* Debris can be bagged safely
- \* Cleanroom and environmentally safe

## TYPICAL PROPERTIES

- \* Linear high density polyethylene
- \* No Carbon or dyes
- \* Size: 40cm diameter x 55cm high (11 gal.)
- \* Will not tribogenerate
- \* Accepts conductive bags and anti-static bags
- \* No outgassing
- \* Natural white colour

### Bin Liner

- \* Pink opaque anti-static polyethylene 1.5 ml
- \* Surface Resistivity: <10<sup>12</sup> Ohms/Sq. ASTM-D-257
- \* Static Decay Rate: 5KV-O Volts < 2 seconds\*\*  
\*\*per Mil-B081705B Type II-Fed. Test Method 101C Method 4046
- \* Size: 60cm x 85cm

TECHNICAL  
DATA  
SHEET



**Copyright  
Electrolube  
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## STATIC DISSIPATIVE WASTE BASKET AND BIN LINERS – Page 2

### PACKAGING

Waste Basket 5 per case  
Bin Liners 50 per case

### ORDER CODE

E5075WB  
E5076BL



This product is distributed on behalf of ACL Staticide, 1960 East Devon Avenue, EIK Grove Village, IL 60007 USA. An ISO9002 certified company.

Tel: 847 981 9212 Fax: 847 981 9278 Website: [www.aclstaticide.com](http://www.aclstaticide.com)

TECHNICAL  
DATA  
SHEET



### **Copyright Electrolube 2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

