

Flux Remover C

Product Code: FRC

PRODUCT DESCRIPTION

Flux Remover C is a non-flammable fast-drying solvent cleaner specially formulated for the quick and efficient removal of flux residues after soldering. It exhibits rapid cleaning and fast evaporation rates.

PRODUCT USE

Spray onto surface to be cleaned liberally and allow to evaporate. The attached brush may be used to remove any stubborn flux residues. Users should take care that all vapours and liquids be cleared from equipment before performing any operations that could result in an ignition source.

FEATURES

- * Non-flammable
- * Excellent removal of greases, oils and flux residues
- * Leaves a perfectly clean, dry surface - conventional solvents often leave greasy deposits which attract dust and dirt.
- * Harmless to most plastics, rubbers, elastomers, and surface coatings.

TYPICAL PROPERTIES

Liquid density, g/cc:	1.33
Boiling Point, °C (°F)	36 (97)
Vapour Pressure, mm Hg (psia)	497 (9.6)
Flash Point, °C (°F) Closed Cup	None

PACKAGING

200g Aerosol with brush attachment

ORDER CODE

FRC200DB

TECHNICAL
DATA
SHEET



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

