

Thermal Printer Cleaner

Product Code: TPC

PRODUCT DESCRIPTION

TPC pens contain an internationally approved cleaning solvent to standards required by the major electronics manufacturers. They are designed for use in the cleaning of thermal print heads for the removal of ink, dust and other contaminants. They are also suitable for cleaning any area where a pen is appropriate.

PRODUCT USE

Print heads, (especially on thermal printers such as those found on electronic scales etc) Safe on most plastics but some painted surfaces should be tested before use. Delicate instrumentation, contacts, tape heads, sensitive components, video equipment, computers, optical and precision instruments, etc.

WARNING

Please note that this product contains a flammable solvent and should not be used near a naked flame, on live equipment or any source of ignition.

FEATURES

- * Cleans thoroughly to a perfectly dry and residue free surface.
- * Will remove contamination from awkward areas
- * Highly effective and economic to use.

TYPICAL PROPERTIES

Colour:	Clear Colourless Liquid
Purity (%):	99.7
Relative Density at 20°C:	0.787
Boiling Point:	82°C
Water Content (%):	0.15 max.
Residue on Evaporation:	0.002g/100ml max.
Flash Point:	12°C

TECHNICAL
DATA
SHEET



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Thermal Printer Cleaner – Page 2

Water Miscibility:
TLV:

Complete
400 ppm

PACKAGING

5 x 12ml fibre tipped pens
(packed 5 packs per box)

ORDER CODE

TPC12P

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

