

Ultraclens

Product Code: ULC

PRODUCT DESCRIPTION

A special blend of solvents for cleaning of critical electro-mechanical applications, and is highly recommended for cold cleaning applications in conjunction with all types of electro-mechanical equipment. **ULC** is also ideal for use in cleaning tanks, as it has a low evaporation rate and high flashpoint. A full range of cleaning solvents are available from **Electrolube**. The range includes fast evaporating solvents and water based cleaners.

PRODUCT USE

For safe, rapid cleaning of all types of electro-mechanical equipment where the use of water-based chemicals is inadvisable. Removes grease, oxides, flux and general dirt. **Ultraclens** is harmless to metals and fabrics under normal conditions and safe to use on most plastics, however a small area should be tested before use.

FEATURES

- * Powerful, penetrating action, works faster than conventional solvents.
- * Lower toxicity than conventional halogenated solvents.
- * High flash point, reducing the risk of fire caused by flammable solvents.
- * 100% Ozone Friendly in both bulk and aerosol forms
- * CO₂ propelled aerosol version available containing 20% more active cleaner.

PROPERTIES

Form:	Clear, Colourless Liquid
Boiling Point:	173-193°C
Freezing Point:	<-50°C
Vapour Pressure @ 38°C:	3.75 mm/Hg (0.5 kPa)
Specific Gravity @ 20°C:	0.79
Viscosity @ 20°C:	1.48
Inhalation Toxicity:	300 ppm
Flash Point:	>60°C

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



UltracLens – Page 2

Residue on Evaporation: <10 ppm

PACKAGING

200 ml Aerosol
400 ml Aerosol
1 Litre Bulk
5 Litre Bulk
25 Litre Bulk

ORDER CODE

ULC200D
ULC400D
ULC01L
ULC05L
ULC25L

NATO Stock No (ULC25L): 6850-99-570-1210

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

